



SAN Immersion Heaters for oil heating etc.

Type BO

Application:

All types are equipped with thermo well and can be delivered with thermostat.
Delivered with terminal box.

Technical data:

Heating element:	Flat profile B, stainless steel, Werkstoff. no. 1.4571, AISI 316Ti
Bushing:	Brass
Terminal box:	Silumine, IP55, no. 70556, for 2" WRG bushing For type BOL: Galvanized box, IP55.

BOL

1"WRG

230V

Type	Power W	Immersion length mm	W/cm ²	Part no.
BOL 20	200	200	1.5	84125
BOL 25	250	200	2.0	84130
BOL 55	550	500	1.5	84135
BOL 75	750	600	2.0	84140

BOCX 1.0W/cm²

2"WRG

3x230/400V

Type	Power kW	Immersion length mm	Part no.
BOCX 60	0.60	300	84100
BOCX 105	1.05	500	84101
BOCX 180	1.80	800	84107
BOCX 210	2.10	1000	84108



SAN Immersion Heaters
for oil heating etc.

Type BO

BODX 1.5W/cm²

2"WRG

3x230/400V

Type	Power kW	Immersion length mm	Part no.
BODX 105	1.05	300	84102
BODX 165	1.65	500	84106
BODX 210	2.10	625	84110
BODX 270	2.70	800	84103
BODX 330	3.30	1000	84115

BOEX 2.0W/cm²

2"WRG

3x230/400V

Type	Power kW	Immersion length mm	Part no.
BOEX 135	1.35	300	84104
BOEX 225	2.25	500	84111
BOEX 270	2.70	625	84113
BOEX 375	3.75	800	84116
BOEX 480	4.80	1000	84117

BOGZ 3.0W/cm²

2"WRG

3x230/400V

Type	Power kW	Immersion length mm	Part no.
BOGZ 195	1.95	300	84109
BOGZ 270	2.70	400	84112
BOGZ 330	3.30	500	84114
BOGZ 420	4.20	625	84118
BOGZ 540	5.40	800	84119
BOGZ 675	6.75	1000	84120