



SAN Immersion Heaters for oil heating etc.

Type BO

Application:

All types are equipped with thermo well and can be delivered with thermostat.
Delivered with terminal box.

Technical data:

Heating element: Flat profile B, stainless steel,
Werkstoff. no. 1.4571, AISI 316Ti

Bushing: Brass

Terminal box: Silumine, IP55, no. 70556, for 2" WRG bushing
For type BOL: Galvanized box, IP55.

BOL

1"WRG

230V

| Type | Power W | Immersion length mm | W/cm ² | Part no. |
|--------|---------|---------------------|-------------------|----------|
| BOL 20 | 200 | 200 | 1.5 | 84125 |
| BOL 25 | 250 | 200 | 2.0 | 84130 |
| BOL 55 | 550 | 500 | 1.5 | 84135 |
| BOL 75 | 750 | 600 | 2.0 | 84140 |

BOCX 1.0W/cm²

2"WRG

3x230/400V

| Type | Power kW | Immersion length mm | Part no. |
|----------|----------|---------------------|----------|
| BOCX 60 | 0.60 | 300 | 84100 |
| BOCX 105 | 1.05 | 500 | 84101 |
| BOCX 180 | 1.80 | 800 | 84107 |
| BOCX 210 | 2.10 | 1000 | 84108 |

SAN Electro Heat a/s

Gillelejevej 30b - DK-3230 Graested - Denmark

Tel.: +45 48 39 88 88 - Fax: +45 48 39 88 98 - info@san-as.com - www.san-as.com

CVR No.: 42 16 59 13

UK:

Harold Comerford
H_comerford@btconnect.com
tel.: +44 1432 851999
mobile: +44 7802 853862

Germany:

Wolfgang Biehs
wolfgang.biehs@nibe.de
tel.: +49 6171 887 724
mobile: +49 1622 793 484

China:

Sun Qiang
qsun@nibechina.com
tel.: +86 21 58366522
mobile: +86 1391 680 5151

Production: Shenzhen, China



SAN Immersion Heaters
for oil heating etc.

Type BO

| BODX 1.5W/cm ² | | 2"WRG | | 3x230/400V | |
|---------------------------|----------|---------------------|----------|------------|--|
| Type | Power kW | Immersion length mm | Part no. | | |
| BODX 105 | 1.05 | 300 | 84102 | | |
| BODX 165 | 1.65 | 500 | 84106 | | |
| BODX 210 | 2.10 | 625 | 84110 | | |
| BODX 270 | 2.70 | 800 | 84103 | | |
| BODX 330 | 3.30 | 1000 | 84115 | | |

| BOEX 2.0W/cm ² | | 2"WRG | | 3x230/400V | |
|---------------------------|----------|---------------------|----------|------------|--|
| Type | Power kW | Immersion length mm | Part no. | | |
| BOEX 135 | 1.35 | 300 | 84104 | | |
| BOEX 225 | 2.25 | 500 | 84111 | | |
| BOEX 270 | 2.70 | 625 | 84113 | | |
| BOEX 375 | 3.75 | 800 | 84116 | | |
| BOEX 480 | 4.80 | 1000 | 84117 | | |

| BOGZ 3.0W/cm ² | | 2"WRG | | 3x230/400V | |
|---------------------------|----------|---------------------|----------|------------|--|
| Type | Power kW | Immersion length mm | Part no. | | |
| BOGZ 195 | 1.95 | 300 | 84109 | | |
| BOGZ 270 | 2.70 | 400 | 84112 | | |
| BOGZ 330 | 3.30 | 500 | 84114 | | |
| BOGZ 420 | 4.20 | 625 | 84118 | | |
| BOGZ 540 | 5.40 | 800 | 84119 | | |
| BOGZ 675 | 6.75 | 1000 | 84120 | | |

SAN Electro Heat a/s

Gillelejevej 30b - DK-3230 Graested - Denmark

Tel.: +45 48 39 88 88 - Fax: +45 48 39 88 98 - info@san-as.com - www.san-as.com

CVR No.: 42 16 59 13

UK:

Harold Comerford
H_comerford@btconnect.com
tel.: +44 1432 851999
mobile: +44 7802 853862

Germany:

Wolfgang Biehs
wolfgang.biehs@nibe.de
tel.: +49 6171 887 724
mobile: +49 1622 793 484

China:

Sun Qiang
qsun@nibechina.com
tel.: +86 21 58366522
mobile: +86 1391 680 5151

Production: Shenzhen, China