




Underfloor Heating Thermostat Type OCC2



Dimensions (mm)



Dimensions (mm)



Connections



4-Event Clock Thermostat

- On/off control up to 3,500W, 16A
- Built-in clock function for automatic comfort and setback temperature
- Set only time and day at installation. Delivered with factory-set program
- With built-in 2-pole interrupter for convenient switching off at airing the room and at summer time
- Adaptive control ensuring comfort temperature at the required time
- Inclined backlit display for better read-out
- Flush mounting in a standard wall socket
- Snap mounting of front cover for easy installation

Technical data:

Supply voltage.....	230V AC +/-15% 50/60Hz
Output relay SPST.....	16A, 3,600W resistive load or 1A inductive load
Built-in interrupter	2-pole, 16A
Temperature range	+5/+40°C
Limitation of range	Min./max.
Clock function	4-event program
Ambient temperature.....	0/40°C during operation
On/off differential.....	0.4°C
Housing	IP21
Sensor type	NTC
Dimensions (H/W/D).....	80/80/48 mm
Size of display (H/W).....	25/22 mm

Elegant European design

Can be mounted in combination with various types of light switches.

Thermostat control

Electronic on/off thermostat for control of temperature by means of a sensor either placed externally or built into the thermostat. The heating output is switched on and off with a differential of only 0.4°C

Housing IP21

Can be mounted in bathrooms and other humid rooms.

Built-in clock function

OCC2 is with built-in 4-event program for automatic comfort and setback temperature.