

Application:

The SAN tubular radiation furnaces are designed for heating of churches, to be mounted below benches or wall-/floor mounting. The construction fulfils the government circular from the Church Ministry concerning implementing and use of church heating systems.

The furnace is designed from powder painted steel tube and equipped with limiter. Silent operation.

Please note when mounting the furnace:

Must be mounted horizontally with the thermostat downwards (marking on radiator).

Power: 200W/m
 Colour: light grey RAL 7032
 Protection class: IP3X
 Approval: EN-60335-2

Other length and power available upon request.
 Other colours available against a surcharge.

Tubular Radiator Furnace Type RO

Part no.	Length, mm	Power, W	Voltage	Surface load
82700500	500	100	230	0,07W/cm ²
82700750	750	150	230	0,07W/cm ²
82701000	1000	200	230	0,07W/cm ²
82701250	1250	250	230	0,07W/cm ²
82701500	1500	300	230	0,07W/cm ²
82701750	1750	350	230	0,07W/cm ²
82702000	2000	400	230	0,07W/cm ²
82702250	2250	450	230	0,07W/cm ²
82702500	2500	500	230	0,07W/cm ²
82702750	2750	550	230	0,07W/cm ²
82703000	3000	600	230	0,07W/cm ²

